




**MAXI-KITE Mk 2 Fitted to
0.5" Heavy Machine Gun**



**MAXI-KITE Mk 2 Fitted to
7.62mm General Purpose
Machine Gun**

MAXI-KITE MK2 Night Sight

- Compact, Lightweight
- Fully Ruggedised
- x6 Magnification
- High Resolution Image
- In-Service
- Simple Operation
- Part of KITE Family

Maxi-Kite Mk 2 is a compact, lightweight night vision sight for use as a portable long range surveillance and weapon sight.

This fully ruggedised system offers x6 magnification and provides a sharp high resolution image for effective observation and target engagement at longer range targets.

Maxi-Kite Mk 2 is part of the highly successful KITE family of night vision equipment, which is currently in-service in more than 50 countries world-wide.

Maxi-Kite Mk 2 is particularly suited for use on longer range weapons such as sniper rifles and other long range large calibre rifles, along with other support weapons such as general purpose machine guns of 7.62mm and 0.50" calibre.

Weapon interface brackets to fit a wide range of weapons can be provided.



MAXI-KITE MK 2 fitted to LSW 5.56mm

MAXI-KITE MK2

Night Sight

Power is derived from two commercially available 1.5V batteries which afford up to 70 hours continuous use. The eyeguard is compatible with NBC clothing and in-service respirators.

Maxi-Kite Mk 2 is simple to operate and its excellent performance is supported by a simple maintenance philosophy, which permits rapid replacement of modular sub assemblies.

Maxi-Kite Mk 2 is in-service with the British Armed Forces and a number of overseas military and security organisations.

Maxi-Kite Mk 2 is supplied complete with transit case, carrying pouch, lens cloth, user handbook, spare batteries, ND Filter and zeroing screwdriver.

> Technical Data

| | |
|--------------------------|---|
| Magnification: | • x6 |
| Field of View: | • 5.5° |
| Weight: | • 1.36kg |
| Length: | • 260mm |
| Height: | • 95mm |
| Width: | • 100mm |
| Power Supply: | • 2 x 1.5V AA Batteries |
| Eyepiece Dioptre: | • Fixed: -1 ± 0.35 dioptre |
| Adjustable: | • +2 -6 dioptre |
| Focus Range: | • 25mm to infinity |
| Eye Relief: | • 30mm |
| Range (minimum): | • Recognition of standing man at 580m in starlight (10 ⁻³) LUX, using 2nd generation II tube. |

THALES